



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H03D 9/06	A1	(11) International Publication Number: WO 00/55965 (43) International Publication Date: 21 September 2000 (21.09.00)
-----------------------------------------------------------------------------	-----------	--------------------------------------------------------------------------------------------------------------------------------

(21) International Application Number: PCT/GB00/00953

(22) International Filing Date: 15 March 2000 (15.03.00)

(30) Priority Data:
9906047.7 17 March 1999 (17.03.99) GB

(71) Applicant (for all designated States except US): THE RESEARCH OF STATE FOR DEFENCE [GB/GB]; Defence Evaluation and Research Agency, Farnborough, Hants GU14 0LX (GB).

(72) Inventors; and


(75) Inventors/Applicants (for US only): MUNDAY, Paul, David [GB/GB]; DERA Malvern, St. Andrews Road, Malvern, Worcestershire WR14 3PS (GB). BARNES, Andrew, Robert [GB/GB]; DERA Malvern, St. Andrews Road, Malvern, Worcestershire WR14 3PS (GB). BALL, Geoffrey [GB/GB]; DERA Malvern, St. Andrews Road, Malvern, Worcestershire WR14 3PS (GB). MOORE, Mark, Terrence [GB/GB]; 27 Ruskington Drive, Wigston, Leicester LE18 1LB (GB). BROWN, Alexander, Lindley [GB/GB]; 9 Britannia Road, North Finchley, London N12 9RU (GB).

(74) Agent: BARKER BRETTELL; 138 Hagley Road, Edgbaston, Birmingham B16 9PW (GB).

(81) Designated States: GB, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published
With international search report.

(54) Title: ELECTROMAGNETIC WAVE RECEIVER FRONT END



(57) Abstract

A receiver front end is provided capable of receiving electromagnetic wave signals having frequencies in the range of substantially 35GHz to substantially 40GHz, and having a gain of substantially 24dB or above and a noise figure of substantially 4dB or below, and comprising one or more multifunction monolithic microwave integrated circuits (MMICs). The receiver front end preferably has a noise figure of substantially 4dB or below over an output signal frequency range of substantially 1 to 10GHz, and a size in the region of 30mm² or less. The receiver front end may comprise a receiver MMIC, and a doubler/buffer amplifier MMIC. The receiver MMIC may comprise a low noise amplifier (3), a mixer (5), a filter (4) and an intermediate frequency amplifier (6).